



LARGE CAN TYPE ALUMINUM ELECTROLYTIC CAPACITORS LSQ

◆ STANDARD SIZE, RATED RIPPLE CURRENT

WV Cap(μF)	10V		16V		25V		35V		50V		63V		80V			
3300													36x50	2.5		
3900													36x50	2.6		
4700													36x50	2.8		
5600												36x50	3.0	36x63	2.9	
6800									36x50	3.3		36x50	3.2	36x83	3.7	
8200									36x50	3.7		36x63	3.8	36x83	4.2	
10000							36x50	3.6	36x50	4.3		36x83	4.1	36x98	5.0	
12000							36x50	3.7	36x63	5.3		36x83	4.4	36x118	5.4	
15000							36x50	4.0	36x83	5.5		36x98	5.5	51x83	7.7	
18000						36x50	5.0	36x63	4.7	36x83	5.7	36x118	6.2	51x83	7.8	
22000					36x63	5.4	36x83	5.6	36x98	6.1	51x83	7.1	51x83	8.0		
27000			36x50	5.1	36x83	5.8	36x83	6.2	36x118	6.7	51x83	7.4	51x98	8.7		
33000			36x63	5.5	36x83	6.0	36x83	6.3	51x83	7.1	51x98	8.8	51x118	10.5		
39000	36x50	5.3	36x83	7.0	36x83	6.7	36x98	7.6	51x83	7.4	51x118	10.0	64x99	12.1		
47000	36x63	6.0	36x83	7.3	36x98	8.0	36x118	8.7	51x98	8.7	64x99	11.9	64x99	14.4		
56000	36x83	6.3	36x98	7.6	36x118	8.4	51x83	10.0	51x98	9.8	64x99	12.6	64x119	15.0		
68000	36x83	7.9	36x98	10.3	51x83	9.3	51x83	10.8	51x118	12.0	64x119	15.0	64x139	16.8		
82000	36x83	8.4	36x118	10.5	51x83	10.0	51x98	12.0	64x99	12.3	77x101	16.4	77x121	19.4		
100000	36x118	9.3	51x83	10.9	51x98	12.0	51x118	13.6	64x119	14.2	77x121	18.9	77x141	21.5		
120000	51x83	10.0	51x98	11.1	51x118	12.9	64x99	13.8	64x119	16.0	77x141	21.6	90x141	22.3		
150000	51x83	11.0	51x98	12.6	64x99	15.3	64x99	14.6	77x121	18.6	90x141	26.0				
180000	51x98	12.1	51x118	13.2	64x99	15.5	64x119	16.7	77x141	19.5						
220000	51x98	14.0	64x99	14.7	64x119	18.0	77x101	17.4	90x141	23.3						
270000	51x118	14.2	64x119	15.4	77x101	18.8	77x141	23.1	90x141	24.8						
330000	64x99	17.3	64x139	18.3	77x121	23.2	77x151	25.9								
390000	64x119	18.0	77x121	19.0	77x141	23.5	90x141	26.5								
470000	64x139	19.3	77x141	22.0	90x141	24.7	90x151	28.3								
560000	77x121	20.1	77x151	23.0	90x141	26.2										
680000	77x141	24.0														

WV Cap(μF)	100V		160V		200V		250V		350V		400V		450V			
270											36x50	1.3	36x50	1.6		
330											36x50	1.7	36x63	1.8		
390									36x50	1.9	36x63	1.8	36x83	2.2		
470							36x50	1.6	36x63	2.1	36x83	2.3	36x83	2.4		
560							36x50	1.6	36x83	2.4	36x83	2.7	36x98	2.8		
680					36x50	1.6	36x50	1.7	36x83	2.9	36x98	2.9	36x118	3.1		
820					36x50	1.7	36x63	1.8	36x98	3.4	36x98	3.4	51x83	3.6		
1000					36x63	2.2	36x83	2.4	36x98	3.8	36x118	3.9	51x83	4.0		
1200			36x50	2.3	36x63	2.3	36x83	2.4	36x118	4.2	51x83	4.2	51x98	4.8		
1500			36x63	3.2	36x83	2.9	36x98	3.1	51x83	4.7	51x98	4.8	51x118	5.7		
1800			36x83	3.4	36x83	2.9	36x118	3.4	51x98	6.3	51x98	5.7	64x99	6.5		
2200	36x50	2.5	36x83	3.6	36x98	3.6	51x83	3.9	51x98	6.4	51x118	7.0	64x99	7.2		
2700	36x50	2.7	36x98	3.8	36x118	4.0	51x83	4.0	64x99	8.8	64x99	7.9	64x119	8.7		
3300	36x50	3.2	36x118	4.7	51x83	4.6	51x98	5.4	64x99	8.8	64x119	9.5	77x121	10.5		
3900	36x63	3.3	51x83	5.3	51x83	4.7	51x118	6.0	64x119	10.3	77x101	10.7	77x121	12.0		
4700	36x83	3.5	51x83	5.6	51x98	7.1	64x99	7.3	77x101	12.0	77x121	12.8	77x141	13.3		
5600	36x83	3.8	51x98	6.4	51x118	8.3	64x99	7.3	77x121	12.7	77x141	14.5	90x141	15.8		
6800	36x98	4.5	51x98	7.5	64x99	9.5	64x119	8.9	77x141	16.0	77x151	17.5	90x151	18.7		
8200	36x118	6.0	51x118	8.1	64x99	10.0	77x101	8.9	90x141	19.0	90x141	18.0				
10000	36x118	6.3	64x99	9.9	64x119	11.1	77x121	11.8	90x141	20.0	90x151	20.5				
12000	51x83	6.6	64x119	10.8	77x101	11.6	77x141	13.1								
15000	51x83	8.5	77x101	12.7	77x121	12.9	90x141	16.5								
18000	51x98	8.9	77x121	14.1	77x141	15.2										
22000	51x118	10.2	77x141	16.6	90x141	15.6										
27000	64x99	11.0	90x141	17.7												
33000	64x119	11.7	90x141	18.9												
39000	77x101	12.5														
47000	77x121	14.5														
56000	77x141	16.2														
68000	77x151	18.3														
82000	90x141	20.1														
100000	90x141	21.0														

Ripple Current A r.m.s./120Hz-85°C
Case Size $\phi D^2 \times L^{\pm 3}$ (mm)

◆ MULTIPLIER FOR RIPPLE CURRENT

(1) Temperature coefficient

Ambient Temperature(°C)	85	70	60≥
Coefficient	1.0	1.6	1.8

(2) Frequency coefficient

Coefficient	Frequency(Hz)					
	60	120	400	1k	10k≤	
	10~50WV	0.80	1.00	1.03	1.05	1.08
63~100WV	0.80	1.00	1.05	1.07	1.10	
160~450WV	0.80	1.00	1.10	1.13	1.18	

*Please notice the following conditions for use.

(1) Maximum screw terminal tightening torque; 33kg·cm or less.

(2) Maximum ripple current shall be 50Arms or less because of the rated current of M5 screw terminal.